

# mysql安装&&配置

## 安装

解压MySQL压缩包/etc/my.cnf/etc/mysql/my.cnf安装MySQL

```
# 配置
log-bin=master-binlog
```

```
# 配置
binlog-format=row
```

```
#配置ID
server-id=1
```

```
# 配置
# binlog-do-db=数据库名
```

```
# 配置
relay-log=relay-bin
```

## 配置

创建用户并授予权限

```
CREATE USER 'replicator'@'%' IDENTIFIED BY 'password';
GRANT REPLICATION SLAVE ON *.* TO 'replicator'@'%';
FLUSH PRIVILEGES;
```

## 启动

启动MySQL服务

server-id=2

# 

--	--	--	--	--	--	--

```
log-bin=master-binlog
```

# 

--	--	--	--	--	--	--

```
binlog-format=row
```

#

```
relay-log=relay-bin
```

# 

--	--	--	--	--	--	--	--

```
# read-only=1
```

[illegible][illegible]

```
SHOW MASTER STATUS;
```

[illegible]

CHANGE MASTER TO

```
MASTER HOST=' 10. 64. 100. 91' ,
```

```
MASTER_USER='replicator',
```

MASTER PASSWORD=' password' ,

```
MASTER LOG FILE=' binlog.000009' ,
```

```
MASTER_LOG_POS=154;
```

# 

--	--	--	--

```
START SLAVE;
```

# 

--	--	--	--	--	--	--

```
SHOW SLAVE STATUS\G;
```

```
# 2
```

```
Slave_IO Running YES
```

```
Slave_SQL Running YES
```

---

```
#1
```

```
21 2024 03:22:59
```

```
21 2024 03:38:23
```