



- windows

```
# windows
```

```
#
```

```
# netsh interface portproxy add v4tov4 listenport=<> listenaddress=<> connectport=<>  
connectaddress=<>
```

```
netsh interface portproxy add v4tov4 listenport=3306 listenaddress=0.0.0.0 connectport=33309  
connectaddress=8.x.y.z
```

```
#
```

```
# netsh interface portproxy delete v4tov4 listenport=<> listenaddress=<>
```

```
netsh interface portproxy delete v4tov4 listenport=3306 listenaddress=0.0.0.0
```

```
#
```

```
netsh interface portproxy show all
```

~~jdbc:mysql://mysql:33306/xxxxx~~~~jdbc:mysql://~~**jdbc:mysql://****\${mysql}:3306/xxxxx**

IDEA

文件

System32\drivers\etc\hosts 只读

H

EasyHosts

更新于 2024/12/19 00:50:17

📄 j-test ✓

双击条目出现✓使生效

📄

📄

📄

📄

📄

⊕ 添加条目

11 # Additionally, comments (such as these) may be inserted on indiv ▲

12 # lines or following the machine name denoted by a '#' symbol.

13 #

14 # For example:

15 #

16 # 102.54.94.97 rhino.acme.com # source server

17 # 38.25.63.10 x.acme.com # x client host

18

19 # localhost name resolution is handled within DNS itself.

20 # 127.0.0.1 localhost

21 # ::1 localhost

22

23

24

25 # Added by Docker Desktop

26 10.0.6.47 host.docker.internal

27 10.0.6.47 gateway.docker.internal

28 # To allow the same kube context to work on the host and the cont

29 127.0.0.1 kubernetes.docker.internal

30 # End of section

31

32

33

34 # --- Add by EasyHosts ---

35 # gzxfgd-test

36 127.0.0.1 mysql

37 127.0.0.1 redis

38

这里是合并后的hosts内容

增加一个分组方便管理

文件

gzhfzd-test

EasyHosts

更新于 2024/12/19 00:50:17

-test

✓

添加条目

1 127.0.0.1 mysql

2 127.0.0.1 redis

将地址解析到本地

#35

18 2024 14:25:16

18 2024 18:37:53